INDUSTRIAL COMPONENT DATA

SACC-E-M12FS-4CON-M16/3,0 1544866 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12FS-4CON-M16/3,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12FS-4CON-M16/3,0
Catalog number	1544866
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-C6870BE89B
Generated	2026-11-19

Product Overview

Panel feed-through
Built-in mount female for sensors/actuators, 4-pole, M12, A-coded, front wall mount/bolt mount, with M16 thread, positionable, with 3.0 m TPE conductor, 4 x 0.34 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1544866
Packing unit 1 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356118316
Weight per Piece (excluding packing) 60.500 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 3 m
Ambient conditions
Degree of protection IP67

General
Rated current at 40°C 4 A
Rated voltage 250 V
Rated surge voltage 2.5 kV
Number of positions 4
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Individual wires
Material
Flammability rating according to UL 94 V0
Cable
Cable type TPE litz wire
Conductor cross section 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation 1.2 mm ±0.07 mm
Thickness, insulation 0.21 mm
Wire colors brown, white, blue, black
Conductor material Tin-plated Cu litz wires
Insulation resistance >= 20 M?*km
Conductor resistance <= 57.6 ?/km
Nominal voltage, cable 300 V
Test voltage, cable 2000 V AC
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 3.0EC002061ETIM 4.0EC002061ETIM 5.0EC002061ETIM 6.0EC002061
UNSPSC 6.0131251501UNSPSC 7.090...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12FS-4CON-M16/3,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.