INDUSTRIAL COMPONENT DATA

SACC-E-M12FS-5CON-PG9/1,0 VAPO 1401204 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12FS-5CON-PG9/1,0 VAPO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12FS-5CON-PG9/1,0 VAPO
Catalog number	1401204
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-4F8C514628
Generated	2026-11-19

Product Overview

Panel feed-through
Conect. plug. to be apar. front wall, 5-pole, M12, Front wall mounting, Pg9, cable length: 1 m, 0.34 mm², TPE braided wire

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1401204
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356538244
Weight per Piece (excluding packing) 31.300 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 1 m
Ambient conditions
Degree of protection IP67
IP69K
General

Rated current at 40°C 4 A
Rated voltage 60 V
Number of positions 5
Insulation resistance > 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA66 GF
Material, knurls Stainless steel
Sealing material FKM
Cable
Cable type TPE litz wire
Conductor cross section 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation 1.2 mm ±0.07 mm
Thickness, insulation 0.21 mm
Wire colors Black, brown,blue, white, gray
Material conductor insulation TPE
Conductor material Tin-plated Cu litz wires
Insulation resistance >= 20 M?*km
Conductor resistance <= 57.6 ?/km
Nominal voltage, cable 300 V
Test voltage, cable 2000 V AC
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027140815eCl@ss 4.127140815eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss 7.0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12FS-5CON-PG9/1,0 VAPO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.