INDUSTRIAL COMPONENT DATA

SACC-E-M12MS-4P-M20/0,15VAPROT 1416039 PHOENIX CONTACT Flush-type connector SACC-E-M12MS-4P-M20/0,15VAPROT 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M12MS-4P-M20/0,15VAPROT



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M12MS-4P-M20/0,15VAPROT
Catalog number	1416039
Category	Sensor-actuator connector chassis
Minimum order	50 Pcs
Document ID	EO-204A5D89D9
Generated	2026-11-18

Product Overview

Flush-type connector - SACC-E-M12MS-4P-M20/0,15VAPROT - 1416039
Conect. plug. to be apar. front wall, 4-pole, Male connector, M12, coding: A, Front mounting, M20 x 1.5, Single braided wires, TPE braided wire, The item does not contain lead according to the RoHS II directive without exception 6c (Pb< 0.1%)
Device connector front mounting, 4-position, Pin, M12, coding: A, Front mounting, M20 x 1,5, Individual wires, cable length: 0.15 m, 0.34 mm2, TPE litz wire, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesNotes on operation The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Safety note
Safety note WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.

• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
• The products are suitable for applications in plant, controller, and electrical device engineering.
• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
• Assembled products may not be manipulated or improperly opened.
• Only use mating connectors th...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M12MS-4P-M20/0,15VAPROT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.