INDUSTRIAL COMPONENT DATA

SACC-EC-M12FS-4CON-PG9/1,5 1508349 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-EC-M12FS-4CON-PG9/1,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-EC-M12FS-4CON-PG9/1,5
Catalog number	1508349
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-3B8601EA42
Generated	2026-11-19

Product Overview

Flush-type connector
Built-in sensor/actuator mounting female, 4-pole, M12, A-coded, front wall mount/bolt-mount, with Pg9 thread, positionable, with 1.5 m TPE conductor, 4x 0.34 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1508349
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4017918889388
Weight per Piece (excluding packing) 39.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 1.5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
Degree of protection IP67

General
Rated current at 40°C 4 A
Rated voltage 250 V
Rated surge voltage 2.5 kV
Number of positions 4
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Individual wires
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA66 GF
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Cable
Cable type TPE litz wire
Conductor cross section 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation 1.2 mm ±0.07 mm
Thickness, insulation 0.21 mm
Wire colors brown, white, blue, black
Material conductor insulation TPE
Conductor material Tin-plated Cu litz wires
Insulation resistance >= 20 M?*km
Conductor resistance <= 57.6 ?/km
Nominal voltage, cable 300 V
Test voltage, cable 2000 V AC
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Download...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-EC-M12FS-4CON-PG9/1,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.