INDUSTRIAL COMPONENT DATA

PSR-SPP-230UC/ESAM4/3X1/1X2/B 2901429 PHOENIX CONTACT Safety relays

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SPP-230UC/ESAM4/3X1/1X2/B



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SPP-230UC/ESAM4/3X1/1X2/B
Catalog number	2901429
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-4E80A71DB0
Generated	2026-11-18

Product Overview

Safety relays
Safety relays for emergency stop control and safety doors up to SIL 3 or cat. 4, PL e according to EN ISO 13849, single or two-channel operation, 3 trip circuits, nominal input voltage: 230 V AC/DC, plug-in push-in terminal block

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data
Orderkey 2901429
Packing unit 1 pc
Catalog page Page 260 (C-6-2017)
GTIN 4046356592208
Weight per Piece (excluding packing) 99.900 g
Custom tariff number 85371098
Country of origin DE (Germany)
Note
Utilization restriction 1
Dimensions
Width 22.5 mm
Height 112 mm

Depth 114.5 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 55 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)
Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)
Maximum altitude <= 2000 m (Above sea level)
Input data
Rated control circuit supply voltage US
Nominal input voltage UN 230 V AC/DC
Input voltage range in reference to UN 0.85 ... 1.1
Typical input current at UN 22 mA
Voltage at input/start and feedback circuit ~ 24 V DC
Typical response time 40 ms (man. start)
Typ. starting time with Us 330 ms (when controlled via A1)
Typical release time 150 ms (when controlled via A1)
20 ms (when controlled via S11/S12 and S21/S22)
Concurrence input 1/2 ?
Recovery time 1 s
Operating voltage display Green LED
Status display Green LED
Protective circuit Surge protection Varistor 275 VRMS(A1-A2)
Surge protection Varistor
Maximum switching frequency 0.5 Hz
Max. permissible overall conductor resistance 50 ?
Output data
Contact type 3 enabling current paths
1 signaling current path
Contact material AgSnO2, + 0.2 µm Au
Maximum switching...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SPP-230UC/ESAM4/3X1/1X2/B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.