INDUSTRIAL COMPONENT DATA

PSR-SPP- 24UC/ESAM4/2X1/1X2 2900526 PHOENIX CONTACT Safety relays

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SPP-24UC/ESAM4/2X1/1X2



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SPP-24UC/ESAM4/2X1/1X2
Catalog number	2900526
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-4E330164EE
Generated	2026-11-19

Product Overview

Safety relays
Safety relay for emergency stop control and safety doors up to SIL 3 or category 4, PL e according to EN ISO 13849, two-channel operation, 2 trip circuits, nominal input voltage: 24 V DC, plug-in push-in terminal block

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data
Orderkey 2900526
Packing unit 1 pc
Catalog page Page 260 (C-6-2017)
GTIN 4046356515665
Weight per Piece (excluding packing) 222.200 g
Custom tariff number 85371098
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 22.5 mm
Height 112 mm

Depth 114.5 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 55 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)
Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)
Maximum altitude <= 2000 m (Above sea level)
Input data
Rated control circuit supply voltage US
Nominal input voltage UN 24 V AC/DC
Input voltage range in reference to UN 0.85 ... 1.1
Typical input current at UN 140 mA AC
65 mA DC
Voltage at input/start and feedback circuit approx. 24 V DC
Typical response time 20 ms (manual start)
150 ms (automatic start)
Typical release time 45 ms (single-channel)
10 ms (two-channel)
Concurrence input 1/2 ?
Recovery time 1 s
Operating voltage display Green LED
Status display Green LED
Protective circuit Surge protection Suppressor diode
Max. permissible overall conductor resistance approx. 50 ? (Input and start circuits at UN)
Output data
Contact type 2 enabling current paths
1 signaling current path
Contact material AgSnO2, + 0.2 µm Au
Maximum switching volta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SPP-24UC/ESAM4/2X1/1X2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.