INDUSTRIAL COMPONENT DATA

CT-TERMIBLOCK 10 DA 0441711 PHOENIX CONTACT Screw termination block

Brand: PHOENIX CONTACT | Manufacturer Part Number: CT-TERMIBLOCK 10 DA



Manufacturer	PHOENIX CONTACT
MPN / Reference	CT-TERMIBLOCK 10 DA
Catalog number	0441711
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-7A980161A0
Generated	2026-11-18

Product Overview

Screw termination block
Block of screw connection terminals with separation contacts for the reception of CT and CTM plug-in protections. Use in MSR and telecommunication systems. Execution: 10 two-wire circuits

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 0441711
Packing unit 10 pc
Catalog page Page 169 (C-4-2017)
GTIN 4017918002213
Weight per Piece (excluding packing) 167.600 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Height 43 mm
Width 118 mm
Depth 40.9 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C
Altitude 2000 m
Degree of protection IP20
General
Housing material PA
Flammability rating according to UL 94 V2
Color black
Standards for cearances and creepage distances IEC 60664-1
Overvoltage category III
Degree of pollution 3
Mounting type DIN rail: 35 mm
Type LSA-PLUS module
Protective circuit
Maximum continuous voltage UC 240 V AC
Operating effective current ICat UC 5 A
Connection data
Connection method Screw terminal blocks
Connection method IN Screw terminal blocks
Connection method OUT Screw terminal blocks
Screw thread M3
Tightening torque 0.5 Nm
Stripping length 7 mm
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section solid 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Environmental Product Compliance
REACh SVHC 4-Nonylphenol, ethoxylated
Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0 27140201 eCl@ss 4.1 27130801 eCl@ss 5.0 27130801 eCl@ss 5.1 27130800 eCl@ss 6.0 27130800 eCl@ss 7.0 27130807 eCl@ss 8.0 27139202 eCl@ss 9.0 27130815
ETIM 2.0 EC000943 ETIM 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CT-TERMIBLOCK 10 DA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.