INDUSTRIAL COMPONENT DATA

# SACB-4Q/4P-L-SC 1662939 PHOENIX CONTACT Sensor/actuator box

**Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-4Q/4P-L-SC**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | SACB-4Q/4P-L-SC |
| Catalog number | 1662939 |
| Category | Passive sensor-actuator interface (with cable) |
| Minimum order | 1 Pcs |
| Document ID | EO-D6D5473F7A |
| Generated | 2026-11-18 |

## Product Overview

Sensor/actuator box
Sensor/Actuator Box, Application: Standard, Connection Type: QUICKON, 0.34 mm² ... 0.75 mm², number of plug-in stations: 4, number of poles: 4, occupation of plug-in stations: single, status indication: Yes, pnp; Main cable connection: Spring connection 180°, shielding: No

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > QUICKON Installation System (QPD) |

## Additional Product Information

Key Commercial Data
Orderkey 1662939
Packing unit 1 pc
Catalog page Page 273 (C-2-2017)
GTIN 4017918137489
Weight per Piece (excluding packing) 166.100 g
Custom tariff number 85366990
Country of origin PL (Poland)
General
Rated voltage 24 V DC
Max. operating voltage Umax 30 V DC
Current carrying capacity per I/O signal 4 A

Current carrying capacity per slot 4 A
Total rated current 12 A
Number of positions 4
Number of slots 4
Flammability rating according to UL 94 V0
Sensor/actuator connection system QUICKON
Ambient conditions
Degree of protection IP65
IP67
Ambient temperature (operation) -25 °C ... 60 °C
Local diagnostics function
Local diagnostics Supply voltage per module Green LED
Status display I/O Yellow LED
Master cable data/connection data
Connection method Spring-cage connection
Conductor cross section min. (signal) 0.14 mm²
Conductor cross section max. (signal) 1 mm²
Conductor cross section AWG min. (signal) 26
Conductor cross section AWG max. (signal) 17
Stripping length (signal) 10 mm
Conductor cross section min. (energy) 0.2 mm²
Conductor cross section max. (energy) 1.5 mm²
Conductor cross section AWG min. (energy) 24
Conductor cross section AWG max. (energy) 16
External cable diameter min. 6.5 mm
External cable diameter max. 9.5 mm
Stripping length 70 mm (Master cable)
Tightening torque, union nut 2.5 Nm
Conductor data
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter Class 2-6 // 0.34 mm²: 0.1 mm; 0.5 - 0.75 mm²: 0.15 mm
Wire insulatio...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB-4Q/4P-L-SC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.