INDUSTRIAL COMPONENT DATA

SACB-6/ 6-M23 1692815 PHOENIX CONTACT Sensor/actuator box

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-6/ 6-M23



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACB-6/ 6-M23
Catalog number	1692815
Category	Passive sensor-actuator interface (with cable)
Minimum order	1 Pcs
Document ID	EO-2AF4526B72
Generated	2026-11-18

Product Overview

Sensor/actuator box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data
Orderkey 1692815
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 114 (PC-2009)
GTIN 4017918177942
Weight per Piece (excluding packing) 117.400 g
Custom tariff number 85366990
Country of origin PL (Poland)
General
Rated voltage 120 V
Max. operating voltage Umax 135 V
Current carrying capacity per I/O signal 2 A
Current carrying capacity per slot 4 A
Total rated current 12 A

Number of positions 4
Number of slots 6
Flammability rating according to UL 94 V0
Sensor/actuator connection system M12 socket
Ambient conditions
Degree of protection IP65
IP67
Ambient temperature (operation) -20 °C ... 75 °C
Master cable data/connection data
Connection method M23 plug connection
Tightening torque slot sensor/actuator cable 0.4 Nm
Insulation material
Housing material PA
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA
Material of contact, master cable side CU alloy
Material of contact surface, master cable side Gold-plated
Material of threaded sleeve PA
O-ring material NBR
Pin assignment
Slot/position = Wire color or connection 1 / 4 (A) = 1
2 / 4 (A) = 2
3 / 4 (A) = 3
4 / 4 (A) = 4
5 / 4 (A) = 5
6 / 4 (A) = 6
1-4 / 1 (+ 120 V) = 11
1-4 / 3 (0 V) = 9+10
1-4 / 5 (PE) = 12
Standards and Regulations
Connection in acc. with standard CUL
Flammability rating according to UL 94 V0
Classifications
eCl@ss 4.027140815eCl@ss 4.127140815eCl@ss 5.027143423eCl@ss 5.127250300eCl@ss 6.027279200eCl@ss 7.027279219eCl@ss 8.027279219e...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB-6/ 6-M23 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.