INDUSTRIAL COMPONENT DATA

SAC-3P-10,0-600/M 8FS VA 1412217 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-10,0-600/M 8FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-10,0-600/M 8FS VA
Catalog number	1412217
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-F616030E1D
Generated	2026-11-18

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 3-pole, halogen-free PP-EPDM, grey RAL 7035, free cable end, to M8 straight connection female, cable length: 10 m, Hygienic design, with stainless steel knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1412217
Packing unit 1 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356951739
Weight per Piece (excluding packing) 201.500 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 10 m
Ambient conditions
Degree of protection IP65

IP67
IP68
IP69K
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 3
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Material conformance FDA 21 CFR 177.2600
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Material
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material of grip body PP
Material, knurls Stainless steel
Sealing material FKM
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Standard designation Material conformance
Standards/regulations FDA 21 CFR 177.2600
Cable
Cable type Halogen-free PP gray
Cable type (abbreviation) 600
Cable abbreviation Li9Y14Y
Conductor cross section 3x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm (Signal line)
Thickness, insulation >= 0.21 mm (Core insulation)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
Length of twist, overall twist 40 mm
External sheath, color gray RAL 7035
Outer sheath thickness...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-10,0-600/M 8FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.