INDUSTRIAL COMPONENT DATA

SAC-3P-M12MS/3,0-PVC 1414435 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12MS/3,0-PVC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12MS/3,0-PVC
Catalog number	1414435
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-9C76F5D382
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 3-pole, PVC, black RAL 9005, Straight male connector M12, coding: A, to free cable end, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1414435
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 196 (C-2-2017)
GTIN 4055626036014
Weight per Piece (excluding packing) 90.160 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 3 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 3
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 HB
Cable
Cable type PVC black
Cable type (abbreviation) PVC
Cable abbreviation LiYY
UL AWM style 2464 / 1729 (80°C/300 V)
Conductor cross section 3x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 19x 0.15 mm
Core diameter including insulation 1.26 mm ±0.05 mm
Thickness, insulation >= 0.23 mm (Core insulation)
Wire colors brown,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12MS/3,0-PVC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.