INDUSTRIAL COMPONENT DATA

SAC-3P- 3,0-PVC/M12FS 1414452 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-3,0-PVC/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-3,0-PVC/M12FS
Catalog number	1414452
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-930640D499
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/Actuator Cable, 3-pole, PVC, black RAL 9005, free cable end, to Straight connection female M12, coding: A, cable length: 3 m
Sensor/actuator cable, 3-position, PVC, black RAL 9005, free cable end, on Socket straight M12, coding: A, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable
Application Standard
Number of positions 3
No. of cable outlets 1
Shielded no
Coding A
Insulation characteristics
Overvoltage category II
Degree of pollution 3
Material specificationsFlammability rating according to UL 94 HB
Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance >= 100 M?
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.4 Nm
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M12
Number of positions 3
Coding type A
Cable/lineCable length 3 m
PVC black [PVC]
Dimensional drawing
Cable weight 40 kg/km
UL AWM Style 2464 / 1729 (80°C/300 V)
Number of positions 3
Shielded no
Cable type PVC black [PVC]
Conductor structure signal line 19x 0.15 mm
AWG signal line 22
Conductor cross section 3x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.26 mm ±0.05 mm
External cable diameter 4.30 mm ±0.2 mm
Outer sheath, material PVC
External sheath, color black RAL 9005
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color brown, blue, black
Thickness,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-3,0-PVC/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.