INDUSTRIAL COMPONENT DATA

SAC-3P-M 8MS/3,0-PVC 1415862 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M 8MS/3,0-PVC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M 8MS/3,0-PVC
Catalog number	1415862
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-9E4FBE4754
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/Actuator Cable, 3-Pole, M8 Straight Connector, Coding: A, To Free Cable End, Cable Length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1415862
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 196 (C-2-2017)
GTIN 4055626053769
Weight per Piece (excluding packing) 70.310 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 3 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65

IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 3
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Status display No
Protective circuit/component unwired
Insertion/withdrawal cycles >= 100
Material
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Cable
Cable type PVC black
Cable type (abbreviation) PVC
Cable abbreviation LiYY
Conductor cross section 3x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 14x 0.15 mm
Core diameter including insulation 1.17 mm ±0.05 mm
Thickness, insulation >= 0.23 mm (Core insulation)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
External sheath, color black RAL 9005
Outer sheath thickness >= 0.76 mm
External cable diameter D 4.2 mm ±0.15 mm
Cable weight 29 kg/km
Outer sheath, material P...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M 8MS/3,0-PVC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.