INDUSTRIAL COMPONENT DATA

SAC-4P-M12MR/0,25PVC/8PFRVA IT 1409683 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MR/0,25PVC/8PFRVA IT

Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MR/0,25PVC/8PFRVA IT
Catalog number	1409683
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-2BDC1F079B
Generated	2026-11-18

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 4-pole, PVC, black RAL 9005, Angled male connector M12, coding: A, to Elbowed connection female M12, coding: A, cable length: 0.25 m, Female connector M12, 8 poles
Sensor/actuator cable, 4-pole, PVC, black RAL 9005, M12 angled male connector, encoding: A, on M12 angled female connector, encoding: A, cable length: 0.25 m, M12 female connector, 8-pin

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1409683
Packing unit 1 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356871761
Weight per Piece (excluding packing) 28.300 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 0.25 m

Ambient conditions
Degree of protection IP65
IP67
IP68
IP69K
General
Rated current at 40°C 4 A
Rated voltage 30 V AC
30 V DC
Number of positions 4
Insulation resistance >= 10 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Stainless steel
Sealing material NBR
Standards and Regulations
Flame resistance As per UL-Style 2464
Flammability rating according to UL 94 HB
Cable
Cable type PVC black
Cable type (abbreviation) PVC
Cable abbreviation LiYY
Conductor cross section 4x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 14x 0.15 mm
Core diameter including insulation 1.17 mm ±0.05 mm
Thickness, insulation >= 0.23 mm (Core insulation)
>= 0.76 mm (Outer cable sheath)
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
External sheath, color black RAL 9005
External cable diameter D 4.4 mm ±0.15 mm
Cable weight 33 kg/km
Outer sheath, material PVC
Material conductor insulation PVC
Cond...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MR/0,25PVC/8PFRVA IT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.