INDUSTRIAL COMPONENT DATA

SAC-5P-10,0-PUO/AD-2L OD 1407294 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-10,0-PUO/AD-2L OD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-10,0-PUO/AD-2L OD
Catalog number	1407294
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-0916473FD5
Generated	2026-11-18

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 5-pole, halogen-free PUR, black RAL 9005, free cable end, to AD valve connector (pressure switch), with 2 LEDs, cable length: 10 m, for outdoor applications, with sterling steel center screw and additional silicone gasket (red)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1407294
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 180 (NTK-2014)
GTIN 4046356774123
Weight per Piece (excluding packing) 658.000 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 10 m
Central screw valve connector M3 x 29

Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C (valve plug)
Degree of protection IP65
IP66K (Observe tightening torque)
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 24 V AC
24 V DC
Number of positions 5
Color handle area black
Insulation resistance >= 100 M?
Standards/regulations Valve connector EN 175301-803
Status display 2 LEDs
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Torque 0.6 Nm ... 0.8 Nm (Valve connector)
Tightening torque 0.8 Nm for IP66K
Material
Flammability rating according to UL 94 V0
Valve plug contact material CuSn
Valve plug contact surface material Sn
Valve plug contact insert material PA 6
Material housing valve plug TPU
Sealing material TPU (Seal molded)
Silicon (Seal snapped in)
Standards and Regulations
Standard designation Valve connector
Standards/regulations EN 175301-803
Flammability rating according to UL 94 V0
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUO
Cable abbreviation Li9Y11Y
Conductor cross section 5x 0.5 mm²
AWG signal line 20
Conductor structure signal line 16x 0.20 mm
Core diameter including insulation 2 mm ±0.05 mm
Wire color...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-10,0-PUO/AD-2L OD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.