INDUSTRIAL COMPONENT DATA

SACC-SQ-M12FS-8CON-20-L180 1408573 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-SQ-M12FS-8CON-20-L180



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-SQ-M12FS-8CON-20-L180
Catalog number	1408573
Category	Circular connector, mounting (PCB)
Minimum order	10 Pcs
Document ID	EO-F0097D07E6
Generated	2026-11-18

Product Overview

Flush-type connector
Conect. plug. to be apar. front wall, Universal, 8-pole, Connecting female, straight, M12-SPEEDCON, coding: A, Front mounting, Square flange, Wave welding, 0.25 mm², Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1238782

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1408573
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 240 (C-2-2013)
GTIN 4046356826464
Weight per Piece (excluding packing) 12.330 g
Custom tariff number 85366990
Country of origin DE (Germany)
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)
Degree of protection IP20
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 2 A
Rated voltage 30 V
Rated surge voltage 0.8 kV
Number of positions 8
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Signal type/category Universal
Status display No
Overvoltage category III
Degree of pollution 3
Connection method Solder pins
Insertion/withdrawal cycles > 100
Torque 3 Nm ... 4 Nm (Installation-side)
Mounting type Front mounting Square flange 20 mm side length
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA 6.6
Material, knurls Zinc die-cast, tin-plated
Sealing material FKM
Cable
Conductor cross section 0.25 mm²
Conductor stru...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-SQ-M12FS-8CON-20-L180 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.