INDUSTRIAL COMPONENT DATA

VS-PPC/PL-IP20-93K-LI/5,0 1419179 PHOENIX CONTACT Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC/PL-IP20-93K-LI/5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC/PL-IP20-93K-LI/5,0
Catalog number	1419179
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-3685118BCA
Generated	2026-11-18

Product Overview

Patch cable
Sercos III cable, shielded, star quad, flexible AWG 22 (7 wire), RAL 3020 (red), RJ45/IP67 push-pull plug, plastic to RJ45/IP20 plug, length: 5 m
Sercos III cable, shielded, quadruple star, AWG 22 flexible (7 wires), RAL 3020 (traffic red), RJ45/IP67 connector, Push-Pull, plastic on RJ45/IP20 connector, length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1419179
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 317 (PC-2011)
GTIN 4046356541244
Weight per Piece (excluding packing) 222.220 g
Custom tariff number 85444210
Country of origin PL (Poland)
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C (cable, fixed installation)

-40 °C ... 70 °C (cable, flexible installation)
General data
Number of positions 4
Characteristics head 1
Material (component) Plastic
Characteristics head 2
Material (component) Plastic
Cable
Cable type Sercos III
Cable type (abbreviation) 93K
UL AWM style 21694 (60°C / 600 V)
Signal type/category Sercos CAT5 (IEC 11801), 100 Mbps
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation approx. 1.55 mm
Wire colors White, yellow, blue, orange
Type of pair shielding Aluminum-lined polyester foil
Overall twist Star quad
Shielding Tinned copper braided shield
External sheath, color signal red RAL 3020
Outer sheath thickness approx. 0.9 mm
External cable diameter D 6.5 mm ±0.2 mm
Minimum bending radius, fixed installation 3 x D
Minimum bending radius, flexible installation 7 x D
Cable weight 68 kg/km
Outer sheath, material PVC
Material, inner sheath PVC
Material conductor insulation PE
Conductor material Tin-plated Cu litz wires
Insulation resistance >= 0.5 G?*km
Conductor resistance <= 120 ?/km
Wave impedance 100 ? ±15 ? (at 100 MHz...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC/PL-IP20-93K-LI/5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.