INDUSTRIAL COMPONENT DATA

EMPPR (27X15) 0829535 PHOENIX CONTACT Shock protection

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMPPR (27X15)



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMPPR (27X15)
Catalog number	0829535
Category	Drawing cover
Minimum order	50 Pcs
Document ID	EO-FB59058D16
Generated	2026-11-18

Product Overview

Shock protection
Protection against accidental contacts, Elbow, transparent, unlabeled, mounting class: interlock, useful surface: 27 x 15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0829535
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 351 (C-3-2017)
GTIN 4046356614931
Weight per Piece (excluding packing) 0.100 g
Custom tariff number 39204910
Country of origin DE (Germany)
Dimensions
Length (b) 15 mm
Width (a) 27 mm
Ambient conditions
Ambient temperature (operation) -30 °C ... 70 °C

Recommended storage conditions 10-30 °C / 40-70 % relative humidity. Storage in a cool and dry place is recommended.
General
Color transparent
Components Silicone-free
Flammability rating according to UL 94 V0
Material PVC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification following DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Foil strength 300 µm
Marking mounting type snapped into marker carrier
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94 V0
Classifications
eCl@ss 10.0.127400629eCl@ss 4.024190218eCl@ss 4.124190218eCl@ss 5.027141137eCl@ss 5.127141100eCl@ss 6.027149100eCl@ss 7.027149129eCl@ss 8.027149129eCl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMPPR (27X15) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.