INDUSTRIAL COMPONENT DATA

KSS 5 2303543 PHOENIX CONTACT Short-circuit connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: KSS 5



Manufacturer	PHOENIX CONTACT
MPN / Reference	KSS 5
Catalog number	2303543
Category	Cross-connector for terminal block
Minimum order	10 Pcs
Document ID	EO-F1C22E6EBB
Generated	2026-11-18

Product Overview

Short-circuit connector
Short-circuit connector, pitch: 5 mm, color: black
Short-circuit connector, pitch: 5 mm, number of positions: 2, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Short-circuit connector
Number of positions 2
Pitch 5 mm
Data management status
Article revision 04
DimensionsPitch 5 mm
Material specificationsColor black (RAL 9005)
Material Copper
Flammability rating according to UL 94 V2
Insulating material PA
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (operation) 20 % ... 90 %
Permissible humidity (storage/transport) 30 % ... 70 %
MountingMounting type Plug-in mounting

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / KSS 5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.