INDUSTRIAL COMPONENT DATA

WMS 12,7 (EX20)RL BK 0800432 PHOENIX CONTACT Shrink sleeve, Roll, black, unlabeled, can be labeled with: THE..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 12,7 (EX20)RL BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 12,7 (EX20)RL BK
Catalog number	0800432
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-1A6E461C5A
Generated	2026-11-18

Product Overview

Shrink sleeve, Roll, black, unlabeled, can be labeled with: THERMOMARK W, THERMOMARK ROLL, THERMOMARK X1.2, THERMOMARK ROLL X1, Unperforated, Mounting type: slide on, Cable diameter: 4.2-12.7 mm, Lettering field: 20 x 80000 mm
Heat-shrink tubing, Roll, black, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, UNDRILLED, MOUNTING CLASS: SLIP, CABLE DIAMETER RANGE: 4.2 ... 12.7 mm, usable area: 20x80000mm, length. Roll: 80 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Dimensions
Length (b) 80 m
Width (a) 20 mm
Cable diameter 4.2 mm ... 12.7 mm
Ambient conditions
Ambient temperature (operation) -55 °C ... 135 °C
General
Color black
Base element material polyolefine

Components Halogen-free
Material Polyolefine
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Marking mounting type slide on

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 12,7 (EX20)RL BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.