INDUSTRIAL COMPONENT DATA

WMS 19,1 (60X30)R CUS 0800742 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 19,1 (60X30)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 19,1 (60X30)R CUS
Catalog number	0800742
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-80764428F0
Generated	2026-11-18

Product Overview

Shrink sleeve
Heat shrink tubing, Roll, white: custom, Perforated, mounting class: sliding, cable diameter range: 6.4 ... 19.1 mm, usable surface: 60 x 30 mm
Shrink sleeve, Roll, white: user-defined, perforated, mounting type: slide-on, cable diameter range: 6.4 ... 19.1 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Shrink sleeve printed
Type Shrink sleeve
Data management status
Article revision 01
Marking
Number of individual labels per row 1
Printing user-defined
Identification technology Thermal transfer for rolls
DimensionsWidth 30 mm
Length 60 mm
External dimensions
Outside diameter 6.4 mm ... 19.1 mm

Material specificationsRoHS compliant yes
Color white (RAL 9010)
Material Polyolefine
Base element material polyolefine
Shrink rate 3:1
Components halogen-free
Shrink temperature > 85 °C
Cable/lineExternal cable diameter 6.4 mm ... 19.1 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 125 °C (150 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-01):2020-03
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Sodium hydroxide 0.1 mol/l
[CAS No. 1310-73-2] Test passed
Ethanol (99 %)
[CAS No.....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 19,1 (60X30)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.