
INDUSTRIAL COMPONENT DATA

WMS 2,4 (60X4)R YE CUS 0800755 PHOENIX CONTACT Shrink sleeve, Roll, yellow, labeled according to customer sp..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 2,4 (60X4)R YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 2,4 (60X4)R YE CUS
Catalog number	0800755
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-C12AADEF4F
Generated	2026-11-18

Product Overview

Shrink sleeve, Roll, yellow, labeled according to customer specifications, Perforated, Mounting type: slide on, Cable diameter: 0.8-2.4 mm, Lettering field: 60 x 4 mm
Heat shrink tubing, Roll, yellow: custom, Perforated, mounting class: slip, cable diameter range: 0.8 ... 2.4 mm, usable surface: 60 x 4 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Dimensions
Length (b) 60 mm
Width (a) 4 mm
Cable diameter 0.8 mm ... 2.4 mm
Ambient conditions
Ambient temperature (operation) -55 °C ... 135 °C
General
Color yellow
Base element material polyolefine
Components Halogen-free
Material Polyolefine
Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels per row 1

Marking mounting type slide on

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 2,4 (60X4)R YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.