INDUSTRIAL COMPONENT DATA

WMS 4,8 (15X9)RL 0800391 PHOENIX CONTACT Shrink sleeve, Roll, white, unlabeled, can be labeled with: THERMOM..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 4,8 (15X9)RL



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 4,8 (15X9)RL
Catalog number	0800391
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-2E34D0F344
Generated	2026-11-18

Product Overview

Shrink sleeve, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X1.2, Perforated, Mounting type: slide on, Cable diameter: 1.6-4.8 mm, Lettering field: 15 x 9 mm
Heat shrink tubing, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, Perforated, mounting class: slip, cable diameter range: 1.6 ... 4.8 mm, usable area: 15x9mm, Number of individual indexes: 4000
Shrink sleeve, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, perforated, mounting type: slide-on, cable diameter range: 1.6 ... 4.8 mm, Number of individual labels: 4000, text field height: 9 mm, text field width: 15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataNotesNote on application For the THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK ROLLMASTER 300/600, and THERMOMARK E.300 (D)/E.600 (D) roll printers, this material can only be processed outside of the printer using the integrated material dispenser pack.
Material information The specified minimum wire diameter of the shrink sleeve refers to its use as a marking material and

does not guarantee any insulation characteristics once shrunk.
Depending on the processed material batch, as well as the storage and processing conditions, the maximum insertable wire diameter may be reduced.
Product propertiesProduct type Shrink sleeve
Type Shrink sleeve
Data management status
Article revision 05
Marking
Number of individual labels 4000
Number of individual labels per row 4
Identification technology Thermal transfer for rolls
DimensionsWidth 9 mm
Text field width 15.00 mm
Text field height 9.00 mm
Length 15 mm
External dimensions
Outside diameter 1.6 mm ... 4.8 mm
Material specificationsRoHS compliant yes
Color white (RAL 9010)
Material Polyolefine
Base element material polyolefine
Shrink rate 3:1
Components halogen-free
Shrink temperature > 85 °C
Cable/lineExternal cable diameter 1.6 mm ... 4.8 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm te...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 4,8 (15X9)RL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.