INDUSTRIAL COMPONENT DATA

WMS 4,8 (60X9)RXL 0800393 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 4,8 (60X9)RXL



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 4,8 (60X9)RXL
Catalog number	0800393
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-9B80A32BB5
Generated	2026-11-18

Product Overview

Shrink sleeve
Heat-shrink tubing, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, UNDRILLED, MOUNTING CLASS: SLIP, CABLE DIAMETER RANGE: 1.6 ... 4.8 mm, usable area: 60x9mm, number of individual indexes: 2500
Heat-shrink sleeve, Roll, white, unlabeled, labelable with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, UNDRILLED, MOUNTING CLASS: SLIP, CABLE DIAMETER RANGE: 1.6 ... 4.8 mm, Number of individual indexes: 2500, text field height: 9 mm, text field width: 60 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0800393
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 233 (C-3-2017)
GTIN 4046356626606
Weight per Piece (excluding packing) 1,232.000 g

Custom tariff number 39173200
Country of origin US (United States)
Dimensions
Length (b) 60 mm
Width (a) 9 mm
Cable diameter 1.6 mm ... 4.8 mm
Ambient conditions
Ambient temperature (operation) -55 °C ... 135 °C
General
Color white
Base element material polyolefine
Type Shrink sleeve
Components halogen-free
Material Polyolefine
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printing without print
Number of individual labels 2500
Number of individual labels per row 1
Marking mounting type slide on
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 4.0 24190219 eCl@ss 4.1 24190219 eCl@ss 5.0 27400401 eCl@ss 5.1 27400100 eCl@ss 6.0 27400100 eCl@ss 7.0 27400105 eCl@ss 8.0 27400105 eCl@ss 9.0 27400401
ETIM 2.0 EC000761 ETIM 3.0 EC001530 ETIM 4.0 EC000217 ETIM 5.0 EC000217 ETIM 6.0 EC001530
UNSPSC 6.01 30211811 UNSPSC 7.0901 39121410 UNSPSC 11 39121410 UNSPSC 12.01 39121410 UNSPSC 13.2 39131504

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 4,8 (60X9)RXL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.