INDUSTRIAL COMPONENT DATA

WMS 50,8 (EX80)R BK CUS 0800735 PHOENIX CONTACT Shrink sleeve, Roll, black, labeled according to customer sp..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 50,8 (EX80)R BK CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 50,8 (EX80)R BK CUS
Catalog number	0800735
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-36A105B992
Generated	2026-11-18

Product Overview

Shrink sleeve, Roll, black, labeled according to customer specifications, Perforated, Mounting type: slide on, Cable diameter: 16.9-50.8 mm
Heat Shrink Tubing, Roll, Black: Customized, Perforated or Cut, Mounting Class: Slip, Cable Diameter Range: 16.9 ... 50.8 mm, usable area: max. 30 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Dimensions
Width (a) 80 mm
Cable diameter 16.9 mm ... 50.8 mm
Ambient conditions
Ambient temperature (operation) -55 °C ... 135 °C
General
Color black
Base element material polyolefine
Components Halogen-free
Material Polyolefine
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Marking mounting type slide on

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 50,8 (EX80)R BK CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.