INDUSTRIAL COMPONENT DATA

WMS-2 HF 3,2 (60X5)RL 0801002 PHOENIX CONTACT Shrink sleeve, roll, white, unmarked, 2:1 shrink ratio, can be..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 3,2 (60X5)RL



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS-2 HF 3,2 (60X5)RL
Catalog number	0801002
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-49DA499544
Generated	2026-11-18

Product Overview

Shrink sleeve, roll, white, unmarked, 2:1 shrink ratio, can be marked with: THERMOMARK ROLL, THERMOMARK X.1, perforated, mounting type: threaded on
Heat shrink tubing, roller, white, unlabeled, 2:1 shrinkage rate, labelable with: THERMOMARK ROLL, THERMOMARK X.1, perforated, mounting type: insertion

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Dimensions
Length (b) 60 mm
Width (a) 5 mm
Cable diameter 1.6 mm ... 3.2 mm
Ambient conditions
Ambient temperature (operation) -30 °C ... 105 °C
General
Color white
Base element material polyolefine
Components Halogen-free
Material Polyolefine
Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 1000
Number of individual labels per row 1
Marking mounting type slide on

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 3,2 (60X5)RL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.