
INDUSTRIAL COMPONENT DATA

WMS 4,8 (EX9)R YE 0800302 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 4,8 (EX9)R YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 4,8 (EX9)R YE
Catalog number	0800302
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-A358C90BF8
Generated	2026-11-19

Product Overview

Shrink sleeve
Heat shrink tubing, Roll, yellow, unlabeled, labelable with: THERMOMARK E.SLEEVE, THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, UNDRILLED, MOUNTING CLASS: SLIP, CABLE DIAMETER RANGE (AUTOMATED PROCESSING): 1.6 ... 4.5 mm, cable diameter range: 1.6 ... 4.8 mm, usable area: 9x30000mm, length. Roll: 30 m
Shrink sleeve, Roll, yellow, unlabeled, can be labeled with: THERMOMARK E.SLEEVE, THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, unperforated, mounting type: slide-on, cable diameter range (automated processing): 1.6 ... 4.5 mm, cable diameter range: 1.6 ... 4.8 mm, Number of individual labels: 1, roll length: 30 m, text field height: 9 mm, text field width: 30000 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataNotesNote on application For the THERMOMARK ROLL and THERMOMARK ROLL 2.0 roll printers, this material can only be processed with an external media hub.
Material information The specified minimum wire diameter of the shrink sleeve refers to its use as a marking material and does not guarantee any insulation characteristics once shrunk.
Depending on the processed material batch, as well as the storage and processing conditions, the maximum insertable wire

diameter may be reduced.
Product propertiesProduct type Shrink sleeve
Type Shrink sleeve
Data management status
Article revision 04
Marking
Number of individual labels 1
Identification technology Thermal transfer for rolls
DimensionsWidth 9 mm
Text field width 30000.00 mm
Text field height 9.00 mm
Length of roll 30.00 m
External dimensions
Outside diameter 1.6 mm ... 4.8 mm
Material specificationsRoHS compliant yes
Color yellow (RAL 1018)
Material Polyolefine
Base element material polyolefine
Shrink rate 3:1
Components halogen-free
Shrink temperature > 85 °C
Cable/lineExternal cable diameter 1.6 mm ... 4.8 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Resu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 4,8 (EX9)R YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.