INDUSTRIAL COMPONENT DATA

SI-H 25MM 0913553 PHOENIX CONTACT Fuse holder

Brand: PHOENIX CONTACT | Manufacturer Part Number: SI-H 25MM



Manufacturer	PHOENIX CONTACT
MPN / Reference	SI-H 25MM
Catalog number	0913553
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-43FA1BCB56
Generated	2026-11-19

Product Overview

Fuse holder
Fuse holder, with accidental contact protection, to cover open fuse contacts, length: 25.5 mm, width: 13 mm, height: 24.5 mm, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 0913553
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4017918008543
Weight per Piece (excluding packing) 2.100 g
Custom tariff number 85389099
Country of origin DE (Germany)
General
Color black
Flammability rating according to UL 94 V2
Dimensions
Width 13 mm

Length 25.5 mm
General
Fuse G / 5 x 20 / 6,3 x 32
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Standards and Regulations
Flammability rating according to UL 94 V2
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SI-H 25MM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.