

INDUSTRIAL COMPONENT DATA**SI-H 40MM 0913566 PHOENIX CONTACT Fuse holder**

Brand: PHOENIX CONTACT | Manufacturer Part Number: SI-H 40MM



Manufacturer	PHOENIX CONTACT
MPN / Reference	SI-H 40MM
Catalog number	0913566
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-E9CB7D8D9C
Generated	2026-09-23

Product Overview

Fuse holder

Fuse holder, with accidental contact protection, to cover open fuse contacts, length: 39.6 mm, width: 14 mm, height: 25 mm, color: black

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **PHOENIX CONTACT > Modular TBs****Additional Product Information**

Key Commercial Data

Orderkey 0913566

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4017918008550

Weight per Piece (excluding packing) 3.930 g

Custom tariff number 85389099

Country of origin DE (Germany)

General

Color black

Flammability rating according to UL 94 V2

Dimensions

Width 14 mm

Length 39.6 mm

General

Fuse G / 5 x 20 / 6,3 x 32

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Standards and Regulations

Flammability rating according to UL 94 V2

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SI-H 40MM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.