INDUSTRIAL COMPONENT DATA

PSR-SCP-24DC/URML4/3X1/1X2/B 2903583 PHOENIX CONTACT Extension module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SCP-24DC/URML4/3X1/1X2/B



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SCP-24DC/URML4/3X1/1X2/B
Catalog number	2903583
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-DC380FF322
Generated	2026-11-19

Product Overview

Extension module
Extension of single- or two-channel contacts for OSSD signals (e.g. light curtain), 3 NO contacts, 1 NC contact, up to category 4, PL e according to EN ISO 13849, SIL 3 according to EN 62061, plug-in screw terminals, width: 22.5 mm
Single or two-channel contact extension for OSSD signals (e.g. light curtain), 3 NO contacts, 1 NC, up to Cat. 4 PL e according to EN ISO 13849, SIL 3 according to EN IEC 62061, pluggable screw terminals, width 22.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data
Orderkey 2903583
Packing unit 1 pc
Catalog page Page 263 (C-6-2017)
GTIN 4046356751698
Weight per Piece (excluding packing) 210.900 g
Custom tariff number 85371098
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions

Width 22.5 mm
Height 99 mm
Depth 114.5 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 55 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)
Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)
Maximum altitude <= 2000 m (Above sea level)
Input data
Rated control circuit supply voltage US
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN 0.85 ... 1.1
Typical input current at UN 70 mA DC
Voltage at input/start and feedback circuit 24 V DC
Typical response time 25 ms (man. start)
Typ. starting time with Us 100 ms (automatic start)
Typical release time 10 ms
Concurrence input 1/2 ?
Recovery time 1 s
Output data
Contact type 3 enabling current paths
1 signaling current path
Contact material AgSnO2
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 15 V AC/DC
Limiting continuous current 6 A (N/C contact / N/O contact)
Maximum inrush current 6 A
Inrush current, minimum 25 mA
Sq. Total current 72 A2(ITH2= I12+ I22+ I32)
Interrupting rating (ohmic load) max. 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SCP-24DC/URML4/3X1/1X2/B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.