INDUSTRIAL COMPONENT DATA

SK U/2,8 P2,54 WH CUS 0825136 PHOENIX CONTACT Marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK U/2,8 P2,54 WH CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK U/2,8 P2,54 WH CUS
Catalog number	0825136
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-1F399AE017
Generated	2026-11-19

Product Overview

Marker strip
Marking strip, Elbow, available: Elbow, white, labelled according to customer specifications, mounting class: glued, for terminal width: 2.54 mm, usable area: 186 x 2.8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0825136
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356354875
Weight per Piece (excluding packing) 9.000 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 186 mm
Width (a) 2.8 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C

Ambient temperature (assembly) > 0 °C
Recommended storage conditions 20-25 °C / 40-50 % relative humidity.
General
Color white
Type adhesive
Components free from silicone and halogen
Material Polyester
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of marker strips 50
Adhesive Acrylic
Printability Office printing systems
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Adhesive strength 20 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Environmental Product Compliance
China RoHS For details about hazardous substances go to ta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK U/2,8 P2,54 WH CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.