INDUSTRIAL COMPONENT DATA

HC-B 16-TMB-100/O1STM40G-EMV 1604450 PHOENIX CONTACT EMC housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 16-TMB-100/O1STM40G-EMV



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 16-TMB-100/O1STM40G-EMV
Catalog number	1604450
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-6F731628C9
Generated	2026-11-19

Product Overview

EMC housing
HEAVYCON ADVANCE EMV B16 aerial housing, with bayonet lock, height 100 mm, with 1x M40 thread, straight cable outlet
HEAVYCON ADVANCE EMC B16 mobile enclosure, bayonet locking, 100 mm height, with 1x M40 thread, straight cable exit

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1604450
Packing unit 10 pc
Note Made to Order (non-returnable)
Catalog page Page 479 (PC-2009)
GTIN 4017918948139
Weight per Piece (excluding packing) 387.940 g
Custom tariff number 85389099
Country of origin DE (Germany)
Dimensions
Height 100 mm

Width 57 mm
Length 126 mm
Length of the assembly cutout 86 mm
Width of the assembly cutout 35 mm
Ambient conditions
Degree of protection of housing (IP) IP65
IP67
Ambient temperature (operation) -40 °C ... 125 °C
General
Note For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K
Size B16
Housing type Sleeve housing
Color gray
Locking type Bayonet locking
No. of cable outlets 1
Cable outlet straight
Screw connection none
Type of the screw connection 1x M40
Housing material Aluminum die-cast
Housing surface material Powder coating
Seal material NBR, conductive
Material grip body interlock PA-GF
Assembly instructions In order to guarantee that the ground conductor contact functions even when plugged in at an angle, the two panel mounting flanges must have sufficient electrical contact with the metal mounting panel.
Connection If insulating powder coating is present on the control cabinet panel, it should be removed from the profile gasket area in order to ensure optimum shielding.
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 16-TMB-100/O1STM40G-EMV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.