INDUSTRIAL COMPONENT DATA

HC-B 24-TMB-100/O1STM32G-STA 1604531 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 24-TMB-100/O1STM32G-STA



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 24-TMB-100/O1STM32G-STA
Catalog number	1604531
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-51AD5BEF49
Generated	2026-11-19

Product Overview

Housing
HEAVYCON ADVANCE with standard powder coating, B24 aerial housing, with bayonet lock, height 100 mm, with 1x M32 thread, straight cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1604531
Packing unit 10 pc
Catalog page Page 565 (PC-2011)
GTIN 4017918948214
Weight per Piece (excluding packing) 468.200 g
Custom tariff number 85389099
Country of origin DE (Germany)
Dimensions
Height 100 mm
Width 57 mm
Length 152 mm
Length of the assembly cutout 112 mm

Width of the assembly cutout 35 mm
Ambient conditions
Degree of protection of housing (IP) IP65
IP67
Ambient temperature (operation) -40 °C ... 125 °C
General
Note for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M
Size B24
Housing type Sleeve housing
Color gray
Locking type Bayonet locking
No. of cable outlets 1
Cable outlet straight
Screw connection none
Type of the screw connection 1x M32
Housing material Aluminum die-cast
Housing surface material Powder-coated, gray
Seal material NBR
Material grip body interlock PA-GF
Assembly instructions In order to guarantee that the ground conductor contact functions even when plugged in at an angle, the two panel mounting flanges must have sufficient electrical contact with the metal mounting panel.
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202
ETIM 2.0EC000437ETIM 3.0EC000437ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437
UNSPSC 6.0131261502UNSPSC 7.090131261502UNSPSC 11...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 24-TMB-100/O1STM32G-STA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.