INDUSTRIAL COMPONENT DATA

SM-7EP1N8A9002 1607063 PHOENIX CONTACT Coupler connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SM-7EP1N8A9002



Manufacturer	PHOENIX CONTACT
MPN / Reference	SM-7EP1N8A9002
Catalog number	1607063
Category	Sensor-actuator connector chassis
Minimum order	12 Pcs
Document ID	EO-1BC926096C
Generated	2026-11-19

Product Overview

Coupler connector
Plug-in coupling connector, Short straight, Screw lock, M40, number of poles: 4+3+PE, contact type: Male, shielded: yes, protection index: IP67, cable diameter range: 9 mm ... 12.5 mm, number of poles: 8, connection type: Crimped connection, series: SM, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1242234

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1607063
Packing unit 12 pc
Note Made to Order (non-returnable)
GTIN 4046356255073
Weight per Piece (excluding packing) 245.940 g
Custom tariff number 85366990
Country of origin DE (Germany)
General
Note Order information: Order crimp contacts 4 x Ø 2 mm, 4 x Ø 3.6 mm separately
Type of locking Screw locking
Coding N

Contact connection method Crimp connection
Type of contacts Pin
Number of positions 8
Contact diameter of power contacts 3.6 mm
Nominal current per power contact at 25°C 70 A
Contact diameter of signal contacts 2 mm
Nominal current per signal contact at 25°C 30 A
Conductor entry 9 mm ... 12.5 mm
Pg housing screw connection none
Ambient conditions
Ambient temperature -40 °C ... 125 °C
Degree of protection IP67
Material
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material PA 6.6
Gasket and O-ring material FPM
Specifications according to DIN EN 61984:2001
Installation height max. 3000 m
Nominal / operating voltage of power contacts 630 V
Rated surge voltage of power contacts 6 kV
Overvoltage category of power contacts III
Degree of pollution of power contacts 3
Nominal / operating voltage of signal contacts 250 V
Rated surge voltage of signal contacts 4 kV
Overvoltage category of signal contacts III
Degree of pollution of signal contacts 3
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SM-7EP1N8A9002 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.