INDUSTRIAL COMPONENT DATA

SM-7EPWN8AA200 1613526 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: SM-7EPWN8AA200



Manufacturer	PHOENIX CONTACT
MPN / Reference	SM-7EPWN8AA200
Catalog number	1613526
Category	Circular connector, mounting (without cable)
Minimum order	6 Pcs
Document ID	EO-8FA9DCC6C7
Generated	2026-11-19

Product Overview

Device connector, front mounting
Conect. plug. to be apar. front wall, angled, fixed, for high loads, SPEEDCON, M40, number of poles: 4+3+PE, contact type: Male, Axial O-ring, 4x Ø4.2, shielded: yes, flange size: 40 mm x 40 mm, protection index: IP67, number of poles: 8, connection type: Crimped connection, series: SM

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1613526
Packing unit 6 pc
Note Made to Order (non-returnable)
GTIN 4046356400848
Weight per Piece (excluding packing) 414.000 g
Custom tariff number 85366990
Country of origin DE (Germany)
General
Note Order information: Order crimp contacts 4 x Ø 2 mm, 4 x Ø 3.6 mm separately
Type of locking SPEEDCON locking
Coding N

Contact connection method Crimp connection
Type of contacts Pin
Number of positions 8
Contact diameter of power contacts 3.6 mm
Nominal current per power contact at 25°C 70 A
Contact diameter of signal contacts 2 mm
Nominal current per signal contact at 25°C 30 A
Pg housing screw connection none
Mounting type 4x Ø4,2
Ambient conditions
Ambient temperature -40 °C ... 125 °C
Degree of protection IP67
Material
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material PA 6.6
Gasket and O-ring material FPM
Specifications according to DIN EN 61984:2001
Installation height max. 3000 m
Nominal / operating voltage of power contacts 630 V
Rated surge voltage of power contacts 6 kV
Overvoltage category of power contacts III
Degree of pollution of power contacts 3
Nominal / operating voltage of signal contacts 250 V
Rated surge voltage of signal contacts 4 kV
Overvoltage category of signal contacts III
Degree of pollution of signal contacts 3
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to ta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SM-7EPWN8AA200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.