

INDUSTRIAL COMPONENT DATA

SMKDSN 1,5/ 5 BD:23-31 1834096 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDSN 1,5/ 5 BD:23-31



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDSN 1,5/ 5 BD:23-31
Catalog number	1834096
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-071EC71C2F
Generated	2026-09-29

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm², number of potentials: 5, number of rows: 1, number of poles per row: 5, article family: SMKDSN 1.5, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1834096

Packing unit 1

GTIN 4046356954501

Custom tariff number 85369010

Dimensions

Length [l] 12 mm

Pitch 5 mm

Dimension a 20 mm

Width [w] 26 mm

Height 11 mm

Height [h] 14.5 mm

Solder pin [P] 3.5 mm

Hole diameter 1.3 mm

General

Range of articles SMKDSN 1,5

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 13.5 A

Nominal cross section 1.5 mm²

Solder pin surface

Internal cylindrical gage A1

Stripping length 6 mm

Number of positions 5

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.14 mm²

2 conductors with same cross section, solid max. 0.75 mm²

2 conductors with same cross section, stranded min. 0.14 mm²

2 conductors with same cross section, stranded max. 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 1 mm²

Standards and Regulations

Connection in acc. with standard...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDSN 1,5/ 5 BD:23-31 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.