
INDUSTRIAL COMPONENT DATA

FKCVR 2,5/10-ST-5,08BKBDWH1-10 1704034 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKCVR 2,5/10-ST-5,08BKBDWH1-10



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKCVR 2,5/10-ST-5,08BKBDWH1-10
Catalog number	1704034
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-D33C913DE3
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 2.5 mm², color: black, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Female connection, Number of potentials: 10, Number of rows: 1, Number of poles per row: 10, number of connections: 10, family of articles: FKCVR 2.5/.. -ST, pitch: 5.08 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 90°, Stecksystem:CLASSIC COMBICON, Lock: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1704034
Packing unit 1
GTIN 4046356672276
Custom tariff number 85366990
Dimensions
Length [l] 26.6 mm
Width [w] 51.42 mm
Height [h] 16.8 mm
Pitch 5.08 mm

Dimension a 45.72 mm
General
Range of articles FKCVR 2,5/..-ST
Number of positions 10
Connection method Push-in spring connection
Rated voltage (III/3) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 1.5 mm²
Minimum AWG according to UL/CUL 26
Maximum AWG according to UL/CUL 12
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above th...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKCVR 2,5/10-ST-5,08BKBDWH1-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.