INDUSTRIAL COMPONENT DATA

SMSTBA 2,5/ 2-G-5,08 GY 1920480 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMSTBA 2,5/ 2-G-5,08 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMSTBA 2,5/ 2-G-5,08 GY
Catalog number	1920480
Category	Printed circuit board connector
Minimum order	2000 Pcs
Document ID	EO-E046FF6BA9
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Printed circuit board base housing, nominal section: 2.5 mm², color: gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: SMSTBA 2.5/.. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.3 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed
PCB base strip, nominal cross-section: 2.5 mm2, color: grey, rated current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact type: pin, number of potentials: 2, number of rows: 1, number of poles: 2, number of terminals: 2, article family: SMSTBA 2.5/.. -G, Pitch: 5.08 mm, Mounting: Wave Soldering, Pin Layout: Linear Pinning, Pin Length [P]: 3.3 mm, Number of Solder Pins per Potential: 1, Plug-in System: COMBICON MSTB 2.5, Mating Face Alignment: Standard, Locking: None, Mounting Type: None, Packaging Type: Packed in a Box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1920480
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)

GTIN 4017918237882
Weight per Piece (excluding packing) 1.660 g
Custom tariff number 85366930
Country of origin DE (Germany)
Dimensions
Length [l] 16.5 mm
Width 12.16 mm
Pitch 5.08 mm
Dimension a 5.08 mm
Width [w] 12.16 mm
Height [h] 18.1 mm
Height 14.8 mm
Length of the solder pin 3.3 mm
Pin dimensions 1 x 1 mm
Length 16.5 mm
General
Range of articles SMSTBA 2,5/..-G
Rated voltage (III/3) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Color gray
Number of positions 2
Standards and Regulations
Connection in acc. with standard EN-VDE
CSA
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002638ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMSTBA 2,5/ 2-G-5,08 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.