
INDUSTRIAL COMPONENT DATA

UCT-PMP (90X38) BU CUS 8190566 PHOENIX CONTACT Snap-in markers

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-PMP (90X38) BU CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-PMP (90X38) BU CUS
Catalog number	8190566
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-12353439E0
Generated	2026-11-18

Product Overview

Snap-in markers
Snap-in sign, blue, labelled according to customer specifications, mounting type: snap onto signage stand, usable surface: 90 x 38mm, Number of individual indexes: 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 8190566
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 287 (NTK-2014)
GTIN 4046356933513
Weight per Piece (excluding packing) 9.990 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 38 mm
Width (a) 90 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color blue
Components free from silicone and halogen
Flammability rating according to UL 94 V0
Material PVC/PC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 1
Number of individual labels per row 1
Printability Direct laser marking
Device 0831831 TOPMARK LASER
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type snapped into marker carrier
Result Test passed
Oxygen index (DIN EN ISO 4589-2) 32.4 %
R22 HL 1 - HL 3
R23 HL 1 - HL 3
R24 HL 1 - HL 3
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flamma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-PMP (90X38) BU CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.