INDUSTRIAL COMPONENT DATA

US-EMP (35X15) YE CUS 0830354 PHOENIX CONTACT Snap-in markers

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-EMP (35X15) YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-EMP (35X15) YE CUS
Catalog number	0830354
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-9CC8A76449
Generated	2026-11-18

Product Overview

Snap-in markers
Sign to fit, available: by card, yellow, labeled according to customer's instructions, mounting class: fit in support for signage, useful surface: 35 x 15 mm, Number of individual indexes: 24

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0830354
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 265 (C-5-2013)
GTIN 4046356715881
Weight per Piece (excluding packing) 14.860 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 15 mm
Width (a) 35 mm
Height (c) 0.5 mm

Ambient conditions
Ambient temperature (operation) -30 °C ... 80 °C
Recommended storage conditions 10-25 °C / 35-65 % relative humidity. Storage in a cool and dry place is recommended.
General
Color yellow
Components Silicone-free
Flammability rating according to UL 94 V0
Material PVC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 24
Number of individual labels per row 3
Printability Thermal transfer
Device 5146464 THERMOMARK CARD
5146451 THERMOMARK CARD-US-MAG1
Ink ribbon 0801371 THERMOMARK-RIBBON 110-TC
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification following DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions IEC 61010-1:2010-06
Result Test passed
Foil strength 500 µm
Marking moun...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-EMP (35X15) YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.