INDUSTRIAL COMPONENT DATA

US-EMP (60X15) SR CUS 0830054 PHOENIX CONTACT Snap-in markers

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-EMP (60X15) SR CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-EMP (60X15) SR CUS
Catalog number	0830054
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-8B9655C2B6
Generated	2026-11-18

Product Overview

Snap-in markers
Sign to fit, available: by card, silver, labeled according to customer's instructions, mounting class: fit in support for signage, useful surface: 60 x 15 mm
Snap-in markers, Card, can be ordered: by card, silver, labeled according to customer specifications, mounting type: snapped into marker carrier, Number of individual labels: 9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Labeled device marker
Data management status
Article revision 01
Marking
Number of individual labels 9
Number of individual labels per row 1
Identification technology Thermal transfer for sheets and cards
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)

Result Test passed
Test duration 96 h
Ambient conditions
Ambient temperature (operation) -30 °C ... 80 °C
Recommended storage conditions 10 ... 25 °C / 35 ... 65 % relative humidity. Storage in a cool and dry place is recommended.
Recommended ambient temperature (storage/transport) 10 °C ... 25 °C
Recommended humidity (storage/transport) 35 % ... 65 %
Shelf life 12 months (see packaging date)
MountingMounting type snapped into marker carrier
Material specificationsRoHS compliant yes
Foil strength 500 µm
Color silver
Material PVC
PVC
Flammability rating according to UL 94 V0
Components Silicone-free
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Ambient conditions
Ambient temperature (operation) -30 °C ... 80 °C
Recommended storage conditions 10 ... 25 °C / 35 ... 65 % relative humidity. Storage in a cool and dry place is recommended.
Recommended ambient temperature (storage/tra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-EMP (60X15) SR CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.