INDUSTRIAL COMPONENT DATA

# HC-B 6-A-UT-PER-F 1648066 PHOENIX CONTACT Terminal adapter

**Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 6-A-UT-PER-F**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | HC-B 6-A-UT-PER-F |
| Catalog number | 1648066 |
| Category | Contact insert for rectangular connectors |
| Minimum order | 5 Pcs |
| Document ID | EO-DAE5006BF6 |
| Generated | 2026-11-18 |

## Product Overview

Terminal adapter
HEAVYCON terminal adapter with female insert, B6 series, 6 poles, for the right side of the control cabinet, screw connection

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |

## Additional Product Information

Key Commercial Data
Orderkey 1648066
Packing unit 5 pc
Minimum order quantity 5 pc
Catalog page Page 545 (C-2-2017)
GTIN 4017918969691
Weight per Piece (excluding packing) 83.780 g
Custom tariff number 85366990
Country of origin CN (China)
Dimensions
Drill hole distance, horizontal 44 mm
Height 74.2 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C
Electrical characteristics
Number of positions 6
Connection in acc. with standard IEC / EN
Rated voltage (III/3) 500 V
Rated surge voltage 6 kV
Rated current 16 A
Mechanical characteristics
Type B6
Screw thread M3
Connection method Screw connection
Tightening torque 0.5 Nm ... 0.8 Nm
Stripping length of the individual wire 12 mm
Conductor cross section 0.5 mm² ... 2.5 mm²
Connection cross section AWG 20 ... 14
General
Note For HEAVYCON-ADVANCE mounting flange and HEAVYCON panel mounting base of B6 type
Connectors may be operated only when there is no load/voltage.
Contact material Copper alloy
Contact surface material Ag
Contact carrier material PA
Standards/regulations PA: Fire protection in rail vehicles - requirement sets R22 and R23 acc. to DIN EN 45545-2 (Risk level HL1 - HL2)
PA: Fire protection in rail vehicles - requirement set R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
Degree of pollution 3
Overvoltage category III
Flammability rating according to UL 94 V0
Connection in acc. with standard IEC / EN
Assembly instructions To ensure correct use, installation in housing with IP54 protection or bett...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 6-A-UT-PER-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.