INDUSTRIAL COMPONENT DATA

SACC-DSI-M 8FS-6CON-M12/0,5 1453465 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M 8FS-6CON-M12/0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M 8FS-6CON-M12/0,5
Catalog number	1453465
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-1974602885
Generated	2026-11-18

Product Overview

Flush-type connector
Conect. plug. to be apar. wall poster., 6-pole, Connecting female, straight, M8, Rear mounting, M12 x 1, Single stranded wires, cable length: 0.5 m, 0.14 mm², PVC conductor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1453465
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 32 (C-2-2017)
GTIN 4046356554398
Weight per Piece (excluding packing) 20.700 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 0.5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Socket)

Degree of protection IP67
General
Rated current at 40°C 1.5 A
Rated voltage 30 V AC
30 V DC
Rated surge voltage 0.8 kV
Number of positions 6
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Individual wires
Torque 1 Nm ... 1.5 Nm (Installation-side)
Mounting type Rear mounting M12 x 1 With flat nut
Material
Flammability rating according to UL 94 HB
Contact material Cu alloy
Contact surface material Au
Contact carrier material PUR / PA 6.6
Material, knurls Nickel-plated brass
Sealing material FKM
Additional material specifications EP (Grout material)
Cable
Cable type PVC litz wire
Conductor cross section 0.14 mm²
AWG signal line 26
Conductor structure signal line 7x 0.16 mm
Core diameter including insulation 1.3 mm ±0.1 mm
Thickness, insulation 0.38 mm
Wire colors Black, brown,blue, white, gray, pink
Material conductor insulation PVC / UL
Conductor material Tin-plated Cu litz wires
Standards/specifications M8 connector IEC 61076-2-104
Insulation resistance >= 20 M?*km
Conductor resistance >= 8...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M 8FS-6CON-M12/0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.