INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FS-8CON-M16 1441817 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FS-8CON-M16



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FS-8CON-M16
Catalog number	1441817
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-ED7A4C8582
Generated	2026-11-18

Product Overview

Panel feed-through
Conect. plug. to be apar. wall poster., 8-pole, Connecting female, M12, coding: A, Rear mount, M16 x 1.5, Wave soldering, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) Item code: 1239740

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1441817
Packing unit 20 pc
Minimum order quantity 20 pc
Note Made to Order (non-returnable)
Catalog page Page 250 (C-2-2013)
GTIN 4046356534017
Weight per Piece (excluding packing) 14.580 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length of the solder pin 6 mm
Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
-40 °C ... 85 °C (without mechanical actuation)
Degree of protection IP67
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 2 A
Rated voltage 30 V
Rated surge voltage 0.8 kV
Number of positions 8
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Solder pins
Insertion/withdrawal cycles > 100
Torque 3 Nm ... 4 Nm (Installation-side)
Mounting type Rear mounting M16 x 1.5 With flat nut
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA 6.6
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Cable
Standards/specifications M12 connector IEC 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FS-8CON-M16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.