INDUSTRIAL COMPONENT DATA

SACC-E-M 8FS-4CON-M8/0,5 1500363 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-M 8FS-4CON-M8/0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-M 8FS-4CON-M8/0,5
Catalog number	1500363
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-EA65DAFFF6
Generated	2026-11-18

Product Overview

Flush-type connector
Conect. plug. to be apar. front wall, 4-pole, Connecting female, straight, M8, Front wall mounting, M8 x 0.5, Single stranded wires, cable length: 0.5 m, 0.25 mm², PVC conductor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1500363
Packing unit 1 pc
Catalog page Page 31 (C-2-2017)
GTIN 4017918589073
Weight per Piece (excluding packing) 12.400 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length of cable 0.5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)
Degree of protection IP67

General
Rated current at 40°C 4 A
Rated voltage 50 V AC
60 V DC
Rated surge voltage 0.8 kV
Number of positions 4
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Individual wires
Torque 0.5 Nm ... 0.6 Nm
Mounting type Front mounting M8 x 0.5
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Au
Contact carrier material PA 6.6
Material, knurls Nickel-plated brass
Sealing material FKM
Additional material specifications EP (Grout material)
Cable
Cable type PVC litz wire
Conductor cross section 0.25 mm²
AWG signal line 24
Conductor structure signal line 7x 0.20 mm
Core diameter including insulation 1.5 mm ±0.1 mm
Thickness, insulation 0.21 mm
Wire colors brown, white, blue, black
Material conductor insulation PVC / UL
Conductor material Tin-plated Cu litz wires
Standards/specifications M8 connector IEC 61076-2-104
Insulation resistance >= 20 M?*km
Conductor resistance >= 80 ?/km
Nominal voltage, cable 300 V
Test voltage, cable 2000 V AC
Ambient temperat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-M 8FS-4CON-M8/0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.