INDUSTRIAL COMPONENT DATA

SACC-SQ-M12FSB-5CON-20/0,5 1441671 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-SQ-M12FSB-5CON-20/0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-SQ-M12FSB-5CON-20/0,5
Catalog number	1441671
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-75394B28A1
Generated	2026-11-19

Product Overview

Flush-type connector
Female mounting incorporated. p/ sensors/actuators, 5 poles, M12, cod. B, front wall mount/square flange mount, TPE twisted wire 0.5 m, 5 x 0.34 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1441671
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 38 (C-2-2017)
GTIN 4046356533010
Weight per Piece (excluding packing) 22.200 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 0.5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)
Degree of protection IP67
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 4 A
Rated voltage 60 V
Rated surge voltage 1.5 kV
Number of positions 5
Insulation resistance >= 100 M?
Coding B - inverse
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Individual wires
Insertion/withdrawal cycles > 100
Torque 3 Nm ... 4 Nm (Installation-side)
Mounting type Front mounting Square flange 20 mm side length
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA 6.6
Material of grip body Zinc die-cast, nickel-plated
Material, knurls Zinc die-cast, nickel-plated
Sealing material FKM
Cable
Cable type TPE l...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-SQ-M12FSB-5CON-20/0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.