INDUSTRIAL COMPONENT DATA

EMG 10-OE- 12DC/ 48DC/100 2948898 PHOENIX CONTACT Solid-state relay module

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMG 10-OE-12DC/ 48DC/100



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMG 10-OE-12DC/ 48DC/100
Catalog number	2948898
Category	Optocoupler
Minimum order	10 Pcs
Document ID	EO-8EC5806163
Generated	2026-11-18

Product Overview

Solid-state relay module
Input solid-state relay, with indicator light and protection circuit in input and output circuit, input: 12 V DC, output: 4 - 48 V DC/max. 100 mA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2948898
Packing unit 10 pc
Catalog page Page 141 (IF-2011)
GTIN 4017918083564
Weight per Piece (excluding packing) 37.970 g
Custom tariff number 85364190
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 10 mm
Height 75 mm

Depth 102 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 60 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Degree of protection IP20
Input data
Nominal input voltage UN 12 V DC
Input voltage range in reference to UN 0.8 ... 1.2
Input voltage range 9.6 V DC ... 14.4 V DC
Switching threshold "0" signal in reference to UN <= 0.4
Switching threshold "1" signal in reference to UN >= 0.8
Typical input current at UN 10 mA
Typical response time 20 µs
Typical turn-off time 100 µs
Status display Yellow LED
Type of protection Reverse polarity protection
Surge protection
Protective circuit/component Polarity protection diode
Transmission frequency 500 Hz
Output data
Output nominal voltage 48 V DC
Output voltage range 4 V DC ... 48 V DC
Limiting continuous current 100 mA
Voltage drop at max. limiting continuous current 0.9 V
Output circuit 2-wire, floating
Type of protection Reverse polarity protection
Surge protection
Protective circuit/component Polarity protection diode
Connection data, input side
Connection name Input side
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cros...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMG 10-OE-12DC/ 48DC/100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.