

INDUSTRIAL COMPONENT DATA

SPT 16/ 3-V-10,0-ZB MCGNYE-GY 1565486 PHOENIX CONTACT Terminal block for printed circuit board, nominal curr..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 16/ 3-V-10,0-ZB MCGNYE-GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 16/ 3-V-10,0-ZB MCGNYE-GY
Catalog number	1565486
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-8E5C4F94FB
Generated	2026-09-26

Product Overview

Terminal block for printed circuit board, nominal current: 76 A, nominal voltage (III/2): 1000 V, nominal section: 16 mm², number of rows: 1, number of poles per row: 3, article family: SPT 16/.. -V, pitch: 10 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: multicolor, Pin arrangement: Zigzag pins W, Pin length [P]: 4.1 mm, number of solder pins per potential: 3, packaging type: boxed PCB terminal, number of poles per row: 3, article family: SPT 16/.. -V, pitch: 10mm, connection type: Push-in spring connection, mounting: Wave soldering, connection direction conductor/printed circuit board: 90°, color: multicolor, Pin arrangement: Zigzag pins W, Pin length [P]: 4.1mm, Packaging type: boxed packaging

PCB terminal block, nominal current: 76 A, rated voltage (III/2): 1000 V, nominal cross section: 16 mm², number of rows: 1, number of positions per row: 3, product range: SPT 16/..-V, pitch: 10 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 90 °, color: multicolored, Pin layout: Zigzag pinning W, Solder pin [P]: 4.1 mm, number of solder pins per potential: 3, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Terminals XL

Product type Printed circuit board terminal

Product family SPT 16/..-V

Number of positions 3
Pitch 10 mm
Number of rows 1
Pin layout Zigzag pinning W
Solder pins per potential 3
Electrical propertiesNominal current IN 76 A
Nominal voltage UN 1000 V
Degree of pollution 3
Rated voltage (III/3) 1000 V
Rated surge voltage (III/3) 8 kV
Rated voltage (III/2) 1000 V
Rated surge voltage (III/2) 8 kV
Rated voltage (II/2) 1000 V
Rated surge voltage (II/2) 6 kV
Connection dataConnection technology
Type PC terminal block can be aligned
Nominal cross section 16 mm²
Conductor connection
Connection method Push-in spring connection
Conductor cross section rigid 0.75 mm² ... 16 mm² (Conductor connection with open terminal point)
0.75 mm² ... 16 mm² (Push-in connection)
Conductor cross section flexible 0.75 mm² ... 16 mm²
Conductor cross section AWG 20 ... 4
Conductor cross section flexible, with ferrule without plastic sleeve 0.75 mm² ... 16 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.75 mm² ... 10 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.75 mm² ... 4 mm²
Stripping length 18 mm
MountingMounting type Wave soldering
Pin layout Zigzag pinning W
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal sur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 16/ 3-V-10,0-ZB MCGNYE-GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.