
INDUSTRIAL COMPONENT DATA

MVSTBW 2,5/17-ST GY 1702131 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBW 2,5/17-ST GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBW 2,5/17-ST GY
Catalog number	1702131
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-AF21369B7B
Generated	2026-11-19

Product Overview

Plug
Connector for printed circuit board, nominal section: 2.5 mm², color: gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 17, number of rows: 1, number of poles: 17, number of connections: 17, family of articles: MVSTBW 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: -90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1702131
Packing unit 1
GTIN 4046356572286
Custom tariff number 85366990
Dimensions
Length [l] 12.5 mm
Width [w] 85 mm
Height [h] 26 mm
Pitch 5 mm
Dimension a 80 mm

General
Range of articles MVSTBW 2,5/..-ST
Number of positions 17
Connection method Screw connection with tension sleeve
Rated voltage (III/3) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 1 mm²
2 conductors with same cross section, stranded min. 0.2 mm²
2 conductors with same cross section, stranded max. 1.5 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 1 mm²
2 conductors with same cross section, strand...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBW 2,5/17-ST GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.