

INDUSTRIAL COMPONENT DATA

SPT 35/ 4-V-15,00 MIX BD:-L3SO 1047746 PHOENIX CONTACT Terminal for printed circuit board, rated voltage: 10..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 35/ 4-V-15,00 MIX BD:-L3SO

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 35/ 4-V-15,00 MIX BD:-L3SO
Catalog number	1047746
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-2852E34B48
Generated	2026-09-28

Product Overview

Terminal for printed circuit board, rated voltage: 1000 V, pitch: 15 mm, number of poles: 4, type of connection: spring clamp push-in, mounting: Soldering wave

Terminal block for printed circuit board, nominal current: 125 A, dimensioning voltage (III/2): 1000 V, nominal section: 35 mm², Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, article family: SPT 35/.. -V, pitch:15 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: multicolor, Pin arrangement: Double linear pin arrangement, Pin length [P]: 5.9mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 35/ 4-V-15,00 MIX BD:-L3SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.